



PATH

GENERAL INFORMATION
THE FOLLOWING SYMBOLS INDICATE THE LOCATION OF FLOOR BOXES CONTAINING UTILITIES AS NOTED:
▲ - 120/208 VOLT SINGLE AND THREE PHASE ELECTRIC.
▲ - ABOVE ELECTRIC PLUS 2" STEAM AND CONDENSATE RETURN, COMPRESSED AIR, COLD WATER AND NATURAL GAS.
■ - ABOVE ELECTRIC PLUS 480 VOLT THREE PHASE ELECTRIC.
● - ALL OF THE ABOVE
○ - 3" DRAIN
■ - 4'-6" SQUARE COLUMNS CHALLS 1 AND D)
■ - 4' SQUARE COLUMNS CHALLS 3,4 AND D)
FIRE-FIRE ALARM
FIRE-FIRE EXTINGUISHER
Ceiling Height = 40' unless indicated
EXHIBIT HALL FLOOR LOAD UNLIMITED EXCEPT OVER UTILITY TUNNEL, WHERE FLOOR LOAD IS 400 LBS./SQ.FT.
■ AREAS MUST REMAIN CLEAR

WASHINGTON COMPLEX (ROOMS A-G)
▲ -120 VOLT SINGLE PHASE ELECTRIC
▲ -120/208 VOLT ELECTRIC ALSO AVAILABLE FROM WALLS AND COLUMNS